

焊接 H 型钢 (YB 3301-81) (一)

1、用途：多用于冶金、建筑等方面。

2、规格

2.1 尺寸及理论重量①

型号	尺寸(mm)					截面面积(cm ²)	理论重量(kg/m)	焊缝厚度(mm)
	H	h	b	d	t			
300*200	300	280	200	6	10	56.8	44.6	5
	300	276	200	6	12	64.6	50.7	5
	300	272	200	8	14	77.8	61.0	6
300*250	300	276	250	8	12	82.1	94.4	6
	300	272	250	10	14	97.2	76.3	6
300*300	300	276	300	8	12	94.1	73.9	6
	300	268	300	10	16	123	96.4	6
	300	260	300	12	20	151	119	8
350*175	350	330	175	6	10	54.8	43.0	5
	350	326	175	8	12	68.1	53.4	6
350*200	350	334	200	6	8	52.0	40.9	5
	350	330	200	8	10	66.4	52.1	6
	350	326	200	8	12	74.1	58.2	6
	350	318	200	10	16	95.8	75.2	6
350*250	350	330	250	8	10	76.4	60.0	6
	350	326	250	8	12	86.1	67.6	6
	350	318	250	10	16	112	87.8	6
350*300	350	326	300	8	12	98.1	77.0	6
	350	318	300	10	16	128	100	6
350*350	350	326	350	8	12	110	86.4	6
	350	318	350	10	16	144	113	6
	350	310	350	12	20	177	139	8
400*200	400	380	200	6	10	62.8	49.3	5
	400	376	200	8	12	78.1	61.3	5
	400	368	200	8	16	93.4	73.4	6
	400	360	200	10	20	116	91.1	6
400*250	400	380	250	6	10	72.8	57.1	5
	400	376	250	8	12	90.1	70.7	5
	400	368	250	8	16	109	85.9	6
	400	360	250	10	20	136	107	6
400*300	400	376	300	8	12	102	80.1	6
	400	368	300	10	16	133	104	6
	400	360	300	12	20	163	128	8

尺寸及理论重量②

型号	尺寸(mm)					截面面积(cm ²)	理论重量(kg/m)	焊缝厚度(mm)
	H	h	b	d	t			
400*400	400	372	400	8	14	142	111	6
	400	368	400	10	16	165	129	8
	400	360	400	12	20	203	160	8
	400	350	400	16	25	256	201	10
	400	336	400	20	32	323	254	12
	400	320	400	25	40	400	314	14
392*400	392	360	400	10	16	164	129	8
410*400	410	360	400	16	25	258	202	10
424*400	424	360	400	20	32	328	258	12
440*400	440	360	400	25	40	410	322	14
450*250	450	426	250	8	12	94.1	73.9	6
	450	418	250	10	16	122	95.6	6
	450	410	250	10	20	141	111	8
450*300	450	426	300	8	12	106	83.3	6
	450	418	300	10	16	138	108	6
	450	410	300	12	20	169	133	8
	450	400	300	12	25	198	155	8
450*400	450	418	400	10	16	170	133	6
	450	410	400	10	20	201	158	8
	450	400	400	12	25	248	195	8
500*250	500	468	250	8	16	117	92.2	6
	500	460	250	10	20	146	115	8
	500	450	250	12	25	179	141	8
500*300	500	468	300	8	16	133	105	6
	500	460	300	10	20	166	130	8
	500	450	300	12	25	204	160	8
500*400	500	468	400	10	16	175	137	6
	500	460	400	10	20	206	162	8
	500	450	400	12	25	254	199	8
600*300	600	568	300	10	16	153	120	6
	600	560	300	10	20	176	138	8
	600	550	300	12	25	216	170	8
600*400	600	568	400	10	16	185	145	6
	600	560	400	10	20	216	170	8
	600	550	400	10	25	255	200	8
	600	540	400	12	30	305	239	8
700*300	700	660	300	10	20	186	146	6
	700	650	300	10	25	215	169	8
	700	640	300	12	30	257	202	8